



PC Board Layout
Component Side Shown

| TOLERANCE UNSPECIFIED | |
|-----------------------|--------|
| .0 | ±0.35 |
| .00 | ±0.25 |
| .000 | ±0.15 |
| X.° | ±2.00° |
| CUSTOMER DRAWING | |

说明:

1. 材质:

胶芯: PA46, UL94V-0; COLOR; BLACK

端子: C5191

外壳: C2680

2. 电镀说明:

端子: 镍底镀金G.F

外壳: 表面镀镍

3. 性能说明:

1) 电压: 150V AC RMS.

2) 额定电流: 1.5A.

3) 接触电阻: 40mΩ Max.

4) 绝缘电阻: 500MΩ MIN.

5) 绝缘耐压: 1000V AC.

6) 工作温度: -40° C TO +80° C.

7) 耐久性: 500 Mating Cycles MIN.

COMPONENT NO:

Smartconn 瀚诚兴科技有限公司
SMARTCONN INT'L H.K CO., LIMITED
HTTP://WWW.SMARTCONN.COM.CN E-mail:sales@smartconn.com.cn

PART NO:

SRJ-0808211SCA

TITLE: RJ45 8P8C 90度带灯左黄右橙PA46

REQUIRED DOCUMENTS: RJ45 8P8C 90度带灯左黄右橙

CHECKED:

SCALE: 1:1 绿PA46

DRAWN: **Engle**

DRAWING:

THIRD ANGLE
PROJECTION

DATE: **2024-07-16**

备注:

